


CHIPPING HAMMERS



AA-00 (R)



AA-20 (R)




PB-20 (R)


OPTION

CHISELS for AA-00 SERIES (Collared type)

Round Shank




Hex. Shank




POINT shape	Overall Length		Part Number	
	mm	in	Round Shank	Hex.Shank
	200	7 7/8"	921-224-0	921-049-0
	176	6 15/16"	877-035-1	921-221-0
	220	8 21/32"	921-225-0	921-220-0

CHISELS for AA & PB SERIES

Round Shank



Hex. Shank



POINT shape	Overall Length		Part Number	
	mm	in	Plain Type	Collared Type
	200	7 7/8"	R 921-021-0	921-072-0
			H 921-025-0	921-075-0
	220	8 21/32"	R 921-003-0	921-070-0
			H 921-010-0	921-073-0
	200	7 7/8"	R 921-056-0	921-071-0
	220	8 21/32"	H 921-055-0	921-074-0



Chisel Retainer Assembly 727-847-6
AA-20,30,40, PB-20,30 Standard Accessories.
(Chisel not included)

SPECIFICATIONS

Recommended Air Pressure : 0.6MPa (85psi)

Model	Chisel Shank Size				Blow Per Min. (about)	Overall Length (about)		Weight Less Chisel (about)		Piston Diameter (about)		Piston Stroke (about)		Air Inlet Thread (Pipe Tap)	Air Hose Size		Average Air Consumption	
	Round		Hexagonal															
	mm	in	mm	in		bpm	mm	in	kg	lb	mm	in	mm		in	in	mm	in
AA-00(R,H)	12.7	1/2	10.5	3/8	2700	228	8 31/32	2.3	5.00	20.0	25/32	50	1 31/32	NPT1/4	9.5	3/8	0.35	12.3
AA-20(R,H)	17.5	5/8	14.7	9/16	2300	270	10 5/8	5.3	11.60	28.0	1 7/64	55	2 5/32	NPT3/8	12.7	1/2	0.60	21.1
AA-30(R,H)	17.5	5/8	14.7	9/16	2000	298	11 23/32	5.7	12.50	28.0	1 7/64	79	3 1/8	NPT3/8	12.7	1/2	0.60	21.1
AA-40(R,H)	17.5	5/8	14.7	9/16	1450	340	13 3/8	6.1	13.40	28.0	1 7/64	111	4 3/8	NPT3/8	12.7	1/2	0.60	21.1
PB-20(R,H)	17.5	5/8	14.7	9/16	1900	350	13 25/32	6.6	14.50	28.5	1 1/8	76	3	NPT3/8	12.7	1/2	0.80	28.0
PB-30(R,H)	17.5	5/8	14.7	9/16	1500	397	15 5/8	7.1	15.60	28.5	1 1/8	102	4 1/62	NPT3/8	12.7	1/2	0.80	28.0