

RIVETING HAMMERS

SUPER VIBRATION-PROOF TYPE



BRH-1UD



BRH-1USD



BRH-5USD



BRH-5UD

SPECIFICATIONS

Recommended Air Pressure : 0.6MPa (85psi)

Model	Riveting Capacity				Blow Per Min. (about)	Overall Length (about)		Weight Less Rivet Set (about)		Piston Diameter (about)		Piston Stroke (about)		Air Inlet Thread (Pipe Tap)	Air Hose Size		Average Air Consumption	
	Duralumin		Steel															
	mm	in	mm	in		bpm	mm	in	kg	lb	mm	in	mm		in	in	mm	in
BRH-1UD (R,H)	3.2	No.5	2.4	No.3	2800	143	5 5/8	1.40	3.1	14.30	9/16	38	1 1/2	NPT1/4	9.5	3/8	0.34	12.0
BRH-5UD (R,H)	6.4	1/4	4.8	No.10	1800	211	8 5/16	1.65	3.6	12.70	1/2	100	4	NPT1/4	9.5	3/8	0.37	13.0
BRH-1USD (R,H)	3.2	No.5	2.4	No.3	2800	272	10 45/64	1.60	3.5	14.30	9/16	38	1 1/2	NPT1/4	9.5	3/8	0.34	12.0
BRH-5USD (R,H)	6.4	1/4	4.8	No.10	1800	340	13 25/64	1.90	4.2	12.70	1/2	100	4	NPT1/4	9.5	3/8	0.37	13.0

STANDARD TYPE



BRH-1U (R)



SBH-0



SBH-1A (R)



BRH-5U (R)



BRH-1US (R)

SPECIFICATIONS

Recommended Air Pressure : 0.6MPa (85psi)

Model	Riveting Capacity				Blow Per Min. (about)	Overall Length (about)		Weight Less Rivet Set (about)		Piston Diameter (about)		Piston Stroke (about)		Air Inlet Thread (Pipe Tap)	Air Hose Size		Average Air Consumption	
	Duralumin		Steel															
	mm	in	mm	in		bpm	mm	in	kg	lb	mm	in	mm		in	in	mm	in
SBH-0	2.3	No.2	-	-	6500	123	4 27/32	0.32	0.7	10.00	25/64	23	29/32	NPT1/8	6.35	1/4	0.10	3.5
SBH-1A(R,H)	2.6	No.3	-	-	4000	209	8 15/64	0.86	1.9	11.11	7/16	56	2 3/16	NPT1/4	6.35	1/4	0.15	5.0
BRH-1U(R,H)	3.2	No.5	2.4	No.3	2800	122	4 15/16	1.05	2.4	14.30	9/16	38	1 1/2	NPT1/4	9.5	3/8	0.34	12.0
BRH-1US(R,H)	3.2	No.5	2.4	No.3	2800	180	7 1/8	1.00	2.2	14.30	9/16	38	1 1/2	NPT1/4	9.5	3/8	0.34	12.0
BRH-1UG(R,H)	3.2	No.5	2.4	No.3	2800	187	7 3/8	1.78	3.9	14.30	9/16	38	1 1/2	NPT1/4	9.5	3/8	0.34	12.0
BRH-5U(R,H)	6.4	1/4	4.8	No.10	1800	189	7 7/16	1.40	3.1	12.70	1/2	100	4	NPT1/4	9.5	3/8	0.37	13.0
BRH-5US(R,H)	6.4	1/4	4.8	No.10	1800	246	9 11/16	1.45	3.2	12.70	1/2	100	4	NPT1/4	9.5	3/8	0.37	13.0
BRH-5UG(R,H)	6.4	1/4	4.8	No.10	1800	258	10 5/32	2.13	4.7	12.70	1/2	100	4	NPT1/4	9.5	3/8	0.37	13.0

STANDARD ACCESSORIES


Model	Retainer Spring	Rivet Sets
SBH-0	①	a,b
SBH-1A (R)	②, ⑤	c,i
BRH-1U (R) Series	②, ⑤	d,i
BRH-1U (H) Series	②, ⑤	
BRH-5U (R) Series	④, ⑤	g,i
BRH-5U (H) Series	④, ⑤	

Rivet Set is not attached to the H type.


*Retainer Spring No. ③ and Rivet Set e/f/h are optional accessories.

SHANK SIZE for BRH-5U(H) series

BRH-5U(H) series



SPRING CHISEL RETAINER 876-179-1



RIVETS for SBH & BRH Series

(mm)

	Retainer Spring		Rivet Set		Model
	Part Number		Part Number		
Round Shank	①	700-810-1	a	920-810-0	SBH-0
	②	705-810-1	c	920-020-0	SBH-1A (R) BRH-1U (R) Series BRH-5U (R) Series
	③	710-811-1	e	920-030-0	SBH-1A (R) BRH-1U (R) Series BRH-5U (R) Series
	④	710-812-1	g	920-040-0	BRH-5U (R) Series
	⑤	876-179-1	i	920-800-0	SBH-1A (R) BRH-1U (R) Series BRH-5U (R) Series